

Safety Fence



Made of high-density extruded polyethylene, it's bright color and light weight make it the perfect choice for all restricted areas, public events, crowd control and construction sites. SAFE-T-FENCE is manufactured through a special process: The vertical strands are double thick, while the horizontal strands remain flexible. As a result, the fence stands exceptionally sturdy, requiring less supports. This saves time and materials on both installation and dismantling. SAFE-T-FENCE is rugged, lightweight, and easy to install. It won't rust, sag, corrode, conduct electricity, and is not affected by extreme temperatures. UV treated.

Specifications:

Description	Properties / Value
Material:	Polyethylene
Color:	Orange
Roll Width:	48" +/- .5
Aperature Size, MDxTD	3.75" x 1.75" +/- .25
Rib Thickness MD:	1/8" +/- .16
TD:	1/4" +/- .16
Unit Weight:	7 lbs. +/- .5
Maximum Tensile Strength MD:	100.33 N per strand
TD:	123.33 N per strand
Ultraviolet Resistance:	2 year exposure resistance
Elongation @ break:	50%+
Min Temp:	-85 degrees F
Max temp:	195 degrees F

Features include:

- ® High visibility OSHA orange
- ® Rugged & Lightweight
- ® Exceptionally Sturdy
- ® UV stable and rot resistant to insure long life

Uses Include:

- ® Construction fencing
- ® Snow fencing
- ® Crowd control, sporting events
- ® Visual barrier

Packaging:

Stock #	Length	Width	Roll Wt.	Pallet Qty.	Pallet Wt.
PSF-50	50'	48"	3.5	56 or 160	500 / 1300
PSF-100	100'	48"	7	42 or 90	700 / 1450

