

Silt Fence

DOT - Series

NY21303616X

State of New York DOT Silt Fence

*** Approved by NYSDOT ***

(For Jobs Let after September 2000)

Specifications:

Physical Properties	Test Method	Minimum Value
Grab Tensile, lbs.	ASTM-D-4632	124
Grab Elongation, %	ASTM-D-4632	W15 x F20
Mullen Burst, psi	ASTM-D-3786	300
Puncture, lbs.	ASTM-D-4833	65
Trapezoidal Tear, lbs.	ASTM-D-4533	65
UV Resistance ² , % ³	ASTM-D-4355	80
AOS, US Seive Number	ASTM-D-4751	30
Flow Rate, gal/min/ft ²	ASTM-D-4491	10
Permittivity	ASTM-D-4491	0.10 sec -1

Packaging:

	NY21303616X
Fabric Width	36"
Roll Length	100'
Post Size	1 1/2" x 1 1/2" x 48"
Post Space	6.25' O.C.
Roll Weight	65 lbs.
Pallet Qty.	25
Pallet Weight	1525 lbs.

NY21303616X Silt Fence is the result of our close work with the New York State Department of Transportation to insure compliance with New York Department of Transportation rules and regulations pertaining to erosion control. Our NY21303616X Silt Fence meets New York State DOT and AASHTO M-288 specifications for its intended use.

Tel: (603) 225-4600
24 Hour Fax Inquiry Line: (603) 228-4604
Toll Free: 1-855-630-7807



U. S. Silt & Site Supply Corporation

P.O. Box 2461
Concord, NH 03302