

# U.S. Silt & Site Supply / Getsco

## DOT Series Silt Fence

# MI363016XL

→ **DOT Approved Fabric**

→ **Heavy Duty Posts**

→ **Lathe Reinforcement**

### Packaging:

Parameter	Value
Fabric Width, Inchs	24
Roll Length, Feet	96'
Post Size, Inches	2" x 2" x 36" (nominal)
Post Spacing, Feet O.C.	6
Roll Weight, lbs.	70
Pallet Qty, lbs.	25
Pallet Weight, lbs.	1750
Lathe, Inches	18

Our MI DOT *Premium Series* Silt Fence was designed to comply with MI DOT rules, regulations and specifications pertaining to Silt Fence / Erosion Control. Utilizing style DOT approved filter fabric and heavy duty 2x2 nominal posts with lathe reinforcement, water is allowed to pass through the fabric, while costly suspended soil particles are trapped to settle to the ground. This restricts the loss of costly jobsite material, keeps roads free of mud, and protects our lakes and streams from harmful silt build-up.

### Specifications:

Property	Test	Min. Roll Value
Grab Tensile, lbs	ASTM-D-4632	124 lbs
Grab Elongation, %	ASTM-D-4632	15% x 20%
Mullen Burst, psi	ASTM-D-3786	300 psi
Punctutre, lbs	ASTM-D-4833	65 lbs
Trapezoid Tear, lbs	ASTM-D-4533	65 lbs
UV Resistance, % SR	ASTM-D-4355	80%
AOS, US Sieve	ASTM-D-4751	30 Seive
Permittivity,(1/sec) Gal/min/sqft	ASTM-D-4491	0.1 sec-1
Flow Rate	ASTM-D-4491	8 gal /min/ft

Tel: (603) 225-4600  
24 Hour Fax Inquiry Line: (603) 228-4604  
Toll Free: 1-855-630-7807



U. S. Silt & Site Supply Corporation /  
Getsco

P.O. Box 2461  
Concord, NH 03302